

Structures Technical Seminar

Jennifer McIntire, P.E.- Bridge Consultant, AL & FL Panhandle





© 2021 Contech Engineered Solutions LLC







UAB ASCE Gulf Coast Symposium 2024











UAB ASCE Gulf Coast Symposium 2024



© 2021 Contech Engineered Solutions LLC







UAB ASCE Roundtable Event 2024











© 2021 Contech Engineered Solutions LLC

Solution Development Design Support • Project Design Worksheet • Specifications • Structure Selection Contract Drawings • Permitting • Silting & Layout • Structural/Fabrication Drawings DYOB • Engineer Estimate Approval Assistance Custom Shape Development Site Simulation Proposal Preparation Horizontal/Vertical Alignment Hydraulics & Scour Support • Design Build Support • Foundations and Load Ratings

Options & Support Specific to Your Project Needs

Agenda

- Structures Overview
 Accolorated Bridge C
- Accelerated Bridge Construction
- Foundation Discussion
- Scour Considerations
- Applications
- Partnering With Contech



Installation Support

Preconstruction Meeting On-Site Installation Assistance Logistics Coordination



Contech Engineered Site Solutions



Bridges & Structures, Stormwater Management, Pipe, Erosion Control and Retaining Walls





Contech: Your Project Partner






Full Design Support

- 100 Year Experience
- All 50 DOTs
- Local Representation

Full Installation Support


- Over 90,000 Installations
- Pre-Con Support
- On-Site Representation Available



https://www.conteches.com/connect




Manufacturing Capabilities



© 2021 Contech Engineered Solutions LLC



Clear Span Bridges





Accelerated Bridge Construction



U.S. Department of Transportation Federal Highway Administration

FHWA Accelerated Bridge Program: Industry Trend

Accelerated Bridge Construction (ABC):

• ABC is bridge construction that uses innovative planning, design, materials, and construction methods in a safe and cost-effective manner to reduce the onsite construction time that occurs when building new bridges or replacing and rehabilitating existing bridges

Prefabricated Bridge Elements and Systems

• PBES are structural components of a bridge that are built offsite, or nearsite of a bridge and include features that reduce the onsite construction time and the mobility impact time that occurs when building new bridges or rehabilitating or replacing existing bridges relative to conventional construction methods.



Accelerated Bridge Construction Process





Efficient Logistics and Assembly






Backfill and Completion



Federal Highway Administration Promoting Innovation in Use of Patented and Proprietary Products

- FHWA allows for proprietary materials, specifications, or processes
- Encourages innovation in
- transportation technology and methods
- Effective October 28, 2019



Construction and Maintenance – Promoting Innovation in Use of Patented and Proprietary Products

AGENCY: Federal Highway Administration (FHWA), U.S. Department of Transportation (DOT) ACTION: Final rule. EFFECTIVE: October 28, 2019

SUMMARY: The FHWA revised its regulations to provide greater flexibility for States to use proprietary or patented materials in Federal-aid highway projects. This final rule rescinds the requirements limiting the use of Federal funds in paying for patented or proprietary materials, specifications, or processes specified in project plans and specifications, thus encouraging innovation in transportation technology and methods.

Executive Summary

The FHWA is revising its regulations at 23 CFR 635.411 to provide greater flexibility for States to use patented or proprietary materials in Federal-aid highway projects. Based on a century- old Federal requirement, the outdated requirements in 23 CFR 635.411(a)–(e) are being rescinded to encourage innovation in the development of highway transportation technology and methods. As a result, State Departments of Transportation (State DOTs) will no longer be required to provide certifications, make public interest findings, or develop research or experimental work plans to use patented or proprietary products in Federal-aid projects. Federal funds participation will no longer be restricted when State DOTs specify a trade name for approval in Federal-aid contracts. In addition, Federal-aid participation will no longer be restricted when a State DOT specifies patented or proprietary materials in design-build Request-for- Proposal documents.

Summary from Federal Highway Administration: "This rulemaking will provide greater flexibility to States to use proprietary or patented materials..."



Contech Structural Plate













Contech Structural Plate

BridgeCor / MULTI-PLATE



Aluminum Structural Plate



© 2021 Contech Engineered Solutions LLC



Soil Structure Interaction







PLATE CORRUGATIONS & THICKNESS – STRUCTURAL VERSATILITY



Structural Plate Has 50% More Galvanized Coating than Corrugated Metal Pipe



Structural Plate Durability

Contributing Factors of Long-Term Durability

- рΗ
- Resistivity
- Hardness \bullet
- External contaminants \bullet
 - Deicing salts
 - Agricultural chemicals lacksquare
- **Abrasion Levels** \bullet



Recommended Environmental Ranges

Installed 1966 Bay of Fundy, ME

Abrasion Levels

Table 2 — FHWA Abrasion Guidelines										
Abrasion Level	Abrasion Condition	Bed Load	Flow Velocity							
1	Non-Abrasive	None	Minimal							
2	Low Abrasion	Minor	< 5							
3	Moderate Abrasion	Moderate	5 - 15							
4	Severe Abrasion	Heavy	> 15							

STEEL $6.0 \le pH \le 10.0$ Resistivity > 2,500 ohm-cm

ALUMINUM $4.0 \le pH \le 9.0$ Resistivity > 500 ohm-cm

(fps)



Lightweight, Bolted Plate Construction



FREIGHT ECONOMY



LIFT AND SET IN PLACE



EFFICIENT ASSEMBLY



HANDLES HIGHWAY LOADING



Structural Plate – Private Driveway Project

• 2022- Springville, AL with US Fish






Structural Plate – In-Situ Rehabilitation

Outstanding features:

In-situ rehabilitation ullet







Structural Plate – In-Situ Rehabilitation

Rivercrest Drive over St. Clair County, AL Engineer: CDG Eng



tu Rehabilitation Engineer: CDG Engineers Logan Martin Lake




Structural Plate – In-Situ Rehabilitation Engineer: CDG Engineers

Rivercrest Drive over Logan Martin Lake St. Clair County, AL







KEYSTONE[®]



CONCRETE

HEADWALL





VIST-A-WALL[®]



STEP-BEVELED END





STEP-BEVELED END WITH CONCRETE

ALUMINUM HEADWALL

Precast – CON/SPAN and BEBO Concrete Arches




























BEBO Arch Systems











Modular Components / Accelerated Installation



PRECAST FOUNDATION



PRECAST ARCH UNIT





PRECAST WINGWALL




TWIN LEAF CONSTRUCTION



PRECAST HEADWALL


CURVED ALIGNMENT





- Moment Diagram for O-Series results in: ullet
 - Maximum positive and negative moment reduced ullet
 - Required A1 and A3 steel areas reduced ullet






O-Series results in:

- Reduction in Concrete and Steel (up to 40%) •
- Longer Lay Lengths (less picks, less installation time) due to reduced weights ullet



O-Series Footing Reactions <u>Minimize Stream Disturbance</u>





<u>CANDE</u>, a <u>Culvert Analysis and Design computer program for the design of a soil</u> structure system.

History of CANDE development

- Before1970's traditional methods dating back to 1930's, where soil loading 0 on the culvert is presumed (guessed)
- In 1972, the Federal Highway Administration (FHWA) began research 0 program
- 1976 First version of CANDE
- 1989 DOS Based
- 2007 Windows Based
- 2015 Newest version

How does CANDE differ from the older traditional methods

FEM that takes into account Soil Structure Interaction 0

Free Download link to TRB at http://www.candeforculverts.com




O-Series modeled in CANDE (Culvert ANalysis and DEsign)

									-3	.126 K	7ft																				
	-						24	1 00					115		eus 186	4 1940	103. 103	-0.	.916 K	/ft	CAM 454	7 46%		100						_	45
80	10	60)	70)	740	3 7 <mark>8</mark>	<u>80</u>	8 00	Ĩ	68 3 974		108 1 77 I		190 1162	111	1 100 100 100 100 100 100 100 100 100 1	1233	1371 1335 1	317 1226	1354 1207	1413 1449	1487	1207	192	103	1648	152	1728	111	183		Ĺ
579	m	69	88	759	71	NI	6 2		หา ก	90 183	1007 1000 1		129 12 138 110	1115 1112	1255 1224	1000 1 1007 1 1007 1		315 1589 1588 - 149	13 12	42 148	188	1226	1557	107	1647	1177	1727	117	167	BA7	21-
576	na -			736	7 7 1	81	55	888 890 - 990	999 972 1010	₩ ¹⁰⁰			15 14	15		7	N 10 1 10	114 1947 20		1411 1447	1475	125	1555 1000	100	1848	IUS 4 6	1728	N 1	180	84	
	17				<u>,</u> 77	N7	. <i>8</i> 7	. MI7	965 <mark>- 1</mark> 991		9								÷ 10	140 HH	161	1924 1977	195	105	IM6 "		1725 1725 1734		1885 1944	114 114	
-50 - 510								11 1 7	500 FIR										4	1454	12	8 13.0	151								-
- <u>1</u>	15	65 1	185 24 7	735	775	215	- 85	85 85	थ्र स्ट क्ष	~										144	142	1922	1953	100 #2	145	2 1 <mark>0</mark> 5	1723 12	ាររ ម	1815	195 17	
174	614	64	f¥	734	774	84	- <mark>-5</mark> 1	84	12											-	1462	101 1 1 1 1 1	192	162	166		172	112	182	162	
575	115	655	85	755	771	85		85	m /~											ć	148	1920	188 I	HI	1991	13	170	171	1001	1	
1 12	N2	182	82	722	m	N2	- 82	l 🔤 🕅	1.5												Ka	220	1560	160	1640	150	128	114	183	180	
្រីឆា	ផា	B	. 41	72	771	an	681	87/~,													1.	1488	1559	1589	1639	מו "	171	174	n 1	1.39	
1	i ii	<u>ç (a</u>	<u>(</u> m);	; 730 ;	70	1 1	- 80	y	-	110	171	1 19 1		*	1	1	<u>к</u> н		i# i	8	1	1	152	158 189	188	ine a	171		<mark>. 173</mark>		
99 11	00 5	843	8	10 1	M (NR .	H#		999 9	7 100	107		11,59	1131	125	138 55 1		154. 5	1991	1485	112	151	1957	197	<u>ព្រ</u>		זתו די די	177 1	177	701 IV	
	80	BHI		78	M	3B	818	88	88	6 119	106	115	11/20	1151	122	157	128	1585	150	1411	18	1911	1586	1586	1805	1178	171	175	16	113	
¥7	đư	647 647	47	IJ	76	3 17	817	87	<u>87</u> 9	5 1018	105	1112	1157	118	123	120	1298	1544	1391	141	1173	1517	1955	195	185	יי א מוו זי א	រករ	រស	175	1125	
5	£6	646	606	725	774	NE	н	M5	605 F	4 1077	1054	111	1135	112	1220	1 273	137	1543	158	1441	H78	196	1254	1594	1654	1674 1674	1714	TTM	1714	1154	
925	806	646	u5 a	13	765	J J5	8 45	B	225 9	5 1016	1052	1110	1155	1187	1219	1284	126	1542	153	1431	1477	1515	1553	193	182	، دیں م	1715	1755	1715	1172	
574	604	644	64	724	754	40k	8 14	E34	L¥ 8	2 105	1062	lica	115 4	118	1218	นธ	126	15#	153	113	1175	194	1952	192	162	1172	נהו	1752	1712	182	



Buried Bridge vs. Bridge At-Grade



At-Grade Bridges compared to Buried Bridges:

- Shorter construction time/phasing means lower initial cost
- Minimal/no long-term maintenance lowers overall life cycle cost
- Shorter construction time minimizes traffic disruption
- Bury utilities in backfill over structure
- Increased safety with limited/no freeze concerns,
 - & no deck maintenance





Buried Bridge vs. Bridge At-Grade







Bridge Type Comparison Chart

	CONVENTIONAL	BURIE		
raffic Disruption*	2 YEARS	5 MONT		
onstruction Time*	2 YEARS	1 YEA		
nitial Cost*	\$8 M	\$5.5 N		
ypical Maintenance*	Deck Overlay every			
	15-18 years. Total Deck Replacement every 30-35 years.	Periodic A replacem		



Project – I-64 Huntington, WV **Owner - WVDOH**


Engineer – Modjeski & Masters **Contractor - Ahearn** and Associates



Buried Bridge vs. Culverts








CULVERTS CONVERT TO BURIED BRIDGES

- Complete system with headwalls, wingwalls and foundations •
- Bottomless structure promotes natural aquatic habitat and ٠ fish/wildlife passage
- Maintenance-free structure lowers overall life cycle cost ٠
- Project specific design to handle all loading requirements ٠
- Long clear spans promote improved hydraulics while . minimizing pier blockage







East Valley Water District Highland, California





East Valley Water District Highland, California






East Valley Water District Highland, California



CON/SPAN O-Series- Bridge Replacement



Madison, AL Blake Bottom Road







Madison, AL Blake Bottom Road



Truss Bridges – Pedestrian and Vehicular





© 2021 Contech Engineered Solutions LLC







CONTINENTAL® BRIDGE

	Weathering	[®] Style Pedestr g Steel Finish Safety Rail Sys					
	D	ESIGNI	ED IN A	CCORDAN	NCE WI	TH AASH	ITO LRFD
С	Clear Width:	□ 6′	□ 8′	□ 10′	□ 12′		
. SELECT	Length:	□ 40′ □ 110′	□ 50′ □ 120′	□ 60′ □ 130′	□ 70′ □ 140′	□ 80′ □ 150′	□ 90′ □ 160′
-		□ 180′		only available wit			
	Deck:	Pressure Tr	eated Wood		Cast-in-Pl (by Others)	lace Concrete	
2. SPECIFY	 Bid Drawin Specification 10-Year Lin Estimate 		у	CONTRACTORS OF A CONTRACTOR OF A CONTRACT	dges apacefordarius sulled to the purchaser's on exercision to the award of scontrom to the deares and control to the deares and donatars, exercisation to excess displayment scattering approximation of the dearest scattering approximation of dearest scatte	<text><list-item><list-item><list-item><list-item><list-item><list-item><list-item><list-item><list-item><list-item><list-item></list-item></list-item></list-item></list-item></list-item></list-item></list-item></list-item></list-item></list-item></list-item></text>	
3. SATISFY	 Stamped Drawings in One Week Bridge Delivery in 6-8 Weeks of Appr Bridge Installation Support Cost-Effective Solution 			oved Drawings			

*IBC & AISC designed EXPRESS Structures also available in 20' - 100' lengths.











Custom Designs & Options

OPTIONS

DECK







Wood

Steel Grate


FINISH







Weathering Steel








*Exclusive 35-year galvanized rust free warranty for vehicular truss.





Freight Economy / Simple Installation







Bessemer Pedestrian Bridge over Highway 150





Bessemer Pedestrian Bridge over Highway 150





Vehicular Truss Bridges











Big R Modular Rolled Girder










Big R Custom Rolled Girder













Foundation Discussion

© 2020 Contech Engineered Solutions LLC



Geotechnical Information Required


- Early Information = Most Efficient Design
- Include Boring Elevation •
- Recommended Soil Bearing Capacity
 - Factored Bearing Resistance (LRFD)
 - Allowable Bearing Capacity (ASD/LFD)
 - Must Specify if Bearing is Net or Gross
- Bearing Strata/Water Table Elevation
- Recommendation of Foundation Type
- Pile Type and Axial/Lateral Capacity (if applicable) \bullet
- Structural Settlement Tolerances 1" Total and 1/2" Differential







Geotechnical Information Required





EXPRESS" Foundations

A precast foundation system that blends the speed of precast with the economy of cast-in-place










STEEL EXPRESS Foundations











CIP FILL PROCESS



Blount County Cleveland Project

2022- Cleveland, AL (Installation December 8, 2022)- ALBC on Steel Express Foundations Structure #34: 16' span x 4'-3" rise, 40 LF





Blount County Cleveland Project

2022- Cleveland, AL: ALBC on Steel Express Foundations, 16'-0" span x 4'-3" rise, 40LF ullet








Scour Considerations







HEC No. 18Evaluate Scour Potential

HEC No.23
Design Guideline 8: Articulating Concrete Block Systems
Design Guideline 19: Concrete Armor



ArmorFlex Articulating Concrete Block System



INVERT PROTECTION

SCOUR **PROTECTION**

DAM **OVERTOPPING**





Closed-Cell Block



Open-Cell Block

© 2021 Contech Engineered Solutions LLC



CHANNEL LINING



Armortec Hard Armor Erosion Systems



PERMANENT









ABILITY TO VEGETATE

© 2021 Contech Engineered Solutions LLC




PROVEN

EFFICIENT



Larkwood Drive Road and Slope Protection Cullman, AL







Larkwood Drive Slope Protection


Cullman, AL







Larkwood Drive Slope Protection Cullman, AL





Larkwood Drive Slope Protection Cullman, AL





A-Jacks Concrete Armor Units



SCOUR PROTECTION

PIER SCOUR PROTECTION

TOE STABLIZATION



OUTLET PROTECTION

A-Jacks Unit







DYOB - Building Blocks to a Successful Project

Solution Development

Design Support

Insta



DYOB[®] | Structural Plate

DYOB® | Precast

DYOB[®] | Modular Rolled Girder



Design Your Own Structural Plate solutions.

Current product options include: Aluminum Box Culvert, BridgeCor®



Design Your Own Precast solutions.

Current product options include: CON/SPAN® & BEBO®




Design Your Own Modular Rolled Girder solutions.

Current product options include: Big R EXPRESS Modular Rolled Girder

www.ContechES.com/DYOB

llation



Design Your Own Truss solutions.


Current product options include: Continental Bridge
& Steadfast Bridges





Contech Design Center | Design Made Easy


Save time by using our interactive design tools that enable you to create customized, project-specific drawings and support documentation for estimates and project meetings.






DYOB - Building Blocks to a Successful Project

Solution Development



www.ContechES.com/DYOB

© 2021 Contech Engineered Solutions LLC







CONTECH

oundation

Structure Info

Bridge Type

Span & Rise

Length (ft.), net

Show Clear Rise? Foundation

End Treatments

Calculated Box Number

Plate Shell Count

Straight Leg Length Inside Flow Area 🛈

Rise Side Angle

oad Shell Type 🛈

Type Toe Plate?

Documents


Toolb

Cleara

Contech Design Center Interface


- Model features
 - Clear rise
 - Calculated values
 - Foundation options
 - Clearance box
- Site Plan Demo
- Export/Submit
- Save functionality
- **Documents**
- Deliverables
 - PDF
 - Image
 - **BIM Model**


PANY	
lbox	Messages:
let Outlet	
rance Site Plan	
ALBC ▼ 24'-7" × 9 ▼ HL-93 ▼ R1 ▼ 45 * Achael Length: 45.25	
© Full Metal ♥ YES ♥	
80	
24.58 (ft)	
9.75 (ft)	
4.3° (deg.)	
5.5 (N)	
205.3 (TFA)	







DYOB[®] at www.conteches.com









Lakemont Business Park - Infrastructure	200637	and a	-	6/170	2013
PAN O-Series O427 27'-0" Span x 6'-8 3/4" Rise	DYOB		1781/0	CYOB	
1 Cell - 75' Long	DYOR		CIVOR		
Fort Mill, South Carolina	BURDT SALE	5		5	



Photo Site Simulation






Building Blocks to a Successful Project

 Solution Development
 Design Support

 ture selection
 Image: Solution Support Supp

- Structure selection
- Engineering Estimates
- Signed and sealed drawings
 - Contract drawings
 - Foundation design




		OOTING CALCULATIO		
208.6		0478 (In Arrist)		
	ton Design Exempts	STRONGS.		
	Owned District In-	dik for ansaring of outstations i	the greatest.	
1.5409				
cover, of effective center	125,000	vertical load, per leg. R.	10.145	
and present the second	10.4	five that percentage	125	
territige rises	8.0.0	holisonarisad, per leg. Pa	1847	
	NE 35-44			
FOOTING INSTR		LAMENFORCES READING 1	HELE.	
tase and (I for yes, I for		Perakter/10.5 8102.1.1		
Failing both (Incl. Separate				
Fucing all		7, * 900 tot		
Total load per the Excelling counting the			1102-1000	
The allocation bet		(+1.808 N-4.01848	task presidential	
Broad addressing has				
Top holing -		9-1523 in 1+ 13534 and		
Actual facility with		Auror 100 per		
Autor Institut		Paramet * 47 per		
	- 100	0.4. UNIO	-	
No 465170 2 44 118 1				
Bendry used not be completed unline propulsion		Percentent W last () 47 3-1, stimule, horses to pro- segment for languaged lasts. Recommend provides (I)		
of Training Asses have of Auggesting		have all 10" implications, that & bo		
Indep February		and impact actual provide and press of ad-		
ENTROPY ADDR	E. FACTORIEL LOADE	RENFORCEMENT (MINUN	L MERINCE LIMPS	
Report # 2.2 M		Per-A43HT0 (815.84		
Barray - 2.43ml		A		
Manager * 2.0 kd		No. 4 4.01 (14)		
Pageson (* 5.5 kd				
9mm*3114f		1 max * \$10000		
16, 153, 548		4 - 81088		
16 + 20.0 m		are 20.14		
$H_{1} = 77$ pai		5 mm = 20.01 km		
min 17.08		6, * 2,210		
Aug. #2.0000		A+ 8120/08		
Aug #5 2027	+ 1.286 _p	I+ 178		
3000 \$1274 Page \$1200		Summer * 28.00 ter		
Aug # 100 (rg		CHECK BHEAP		
Tarbara + A	HE TO A	N5448		
Sang have + 8	14日 日本	44, + 26.8 km		
	100	Destant in a		

lation



Building Blocks to a Successful Project

- Attending Pre-Bid Meetings \bullet
- Holding Preconstruction Meeting •
- Technical Support Available (Field Consultant on all Precast Installations) ${\color{black}\bullet}$





Installation



Questions?

CROSSINGS. CULVERTS. BRIDGES. CONTECH.

Jennifer McIntire, P.E. (205) 306-3277 Jennifer.Mcintire@ContechES.com



